

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
2 June 2005 (02.06.2005)




PCT

(10) International Publication Number
WO 2005/050975 A1

- (51) International Patent Classification⁷: **H04N 1/00**
- (21) International Application Number:
PCT/JP2004/017327
- (22) International Filing Date:
16 November 2004 (16.11.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2003-389927 19 November 2003 (19.11.2003) JP
- (71) Applicant (for all designated States except US): **MAT-SUSHITA ELECTRIC INDUSTRIAL CO.,LTD.**
[JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka 5718501 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **YOKOTA, Kaoru.**
FUTA, Yuichi. **NAKANO, Toshihisa.** **OHMORI, Motoji.** **OHKI, Shuichi.**
- (74) Agents: **NAKAJIMA, Shiro** et al.; 6F, Yodogawa 5-Bankan, 2-1, Toyosaki 3-chome, Kita-ku, Osaka-shi, Osaka 5310072 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

[Continued on next page]

(54) Title: DIGITAL CAMERA SYSTEM WITH MEANS FOR RESTRICTING IMAGE ACQUISITION



(57) Abstract: A digital camera comprising: an imaging unit operable to generate an image by photographing an object; a receiving unit operable to receive information relating to image processing from one or more transmission devices; a judging unit operable to judge whether the image is to be output or not, based on the information received by the receiving unit; and an output unit operable to, in accordance with the judgment made by the judging unit, output the image to a memory, or discard the image, where the memory is readable by the digital camera or an external device.



SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*